GOODWE

EzLogger Pro

EzLogger Pro is a self-developed monitoring device by GoodWe. In combination with a GoodWe solar inverter, it can easily read and record all key plant data and constantly transmit the data to the GoodWe portal via internet.



- Communication distance up to 1000m
- Connectivity for up to 60 devices at once
- Data Breakpoint Resume
- Encrypted Data Transmission Process

Communication Management		
Communication	Inverter Communication	3 × RS485
	PC Communication	10 / 100M Ethernet
Number of Managed Devices	RS485	60 (The number of devices connected to a single RS485 port shall not exceed 20)
Communication Distance	RS485 (m)	1000 (Shielded twisted pair wire shall be used)
	Ethernet(m)	100

General Parameters		
General Parameters	Power Adapter	Input: 100 ~ 240Vac, 50 / 60Hz;
		output: 12Vdc 1.5A;
	Power Consumption (W)	General 3, Maximum 6
	Storage Capacity	16MB, expandable to 8GB through an optional SD card
	Dimensions (L × W × H mm)	190 × 118 ×37
	Weight (g)	500
	Operating Temperature Range(°C)	-20 ~ +60
	Relative Humidity (non-condensing)	5% ~ 95%
	Ingress Protection Rating	IP20
	Installation Methods	Wall mounting, table surface mounting, rail mounting
	User Interface	8 LED indicators

*: Please visit GoodWe website for the latest certificates.

GoodWe-Single page-20220927-EN-V1.1. Information may be subject to change without notice during product improving.

sales@goodwe.com service@goodwe.com www.goodwe.com